

# RRC-MC20-180-10

Battery Mating Connector P/N: 210518



## Features:

- Mating connector for standard battery form factors RRC20xx
- 10.00A max. charge or discharge current to battery
- 5-pin male connector
- 5mm pitch
- RoHS and REACH compliant

# **Applications:**

Mating connector for RRC's smart batteries used in medical, industrial and consumer applications

# **TECHNICAL DATA SHEET**

RRC-MC20-180-10



# Specification

Ratings	
Current	10.00A max. / pin
Voltage	125.00VAC / 1min
Materials	
Housing	Thermoplastic High Temperature, UL 94 V-0, black
Contacts	Copper Alloy
Plating	80µin Nickel on contact area, 100µin Matte-Tin on solder tails
Environmental Condition	
Operating Temperature	-55°C to +105°C
Electrical Requirements	
Contact Resistance	30mOhm max.
Insulation Resistance	100mOhm min. at 500VDC / 2min
Dielectric withstand	500.00V
Mechanical Requirements	
Dimensions (LxWxH)	25mm x 11.70mm x 9.80mm
Weight	Typical 3g
PCB mounting	180°
Contact Retention Force	500g min. / pin
Durability	5000 cycles
Physical Requirements	
Solder Temperature	$260\% \pm 5\%$
Immersion Period	SSEC (EIA-364-56C)
Regulatory Approvals	
Green Procurement	RoHS
	КЕАСП
Packaging	
24 connectors per tube	

110 tubes per carton

# **TECHNICAL DATA SHEET**

RRC-MC20-180-10

### Drawings











Tolerance (unless otherwise specified)					
Χ.	X.° ± 10°				
X.X ± 0.38	X.X° ± 5°				
X.XX ± 0.25	X.XX° ± 2°				
X.XXX ± 0.13	X.XXX°				

### All dimensions in mm.

#### Note

- The hooks of the connector fit tightly when a drill hole diameter of 1.05 mm is used, thus making the connection very robust. However, insertion of the connector into the 1.05 mm drill hole requires force and will most likely only be possible with manual assembly.
- In an automated assembly process where force application is not possible, a drill hole diameter of 1.2 mm could be used. However, when fitting the connector into the 1.2 mm drill hole, one must remember that the connector can be removed with minimal effort, thus making the connection less robust.

Germany/HQ	USA	Hong Kong	China	Vietnam
RRC power solutions GmbH	RRC power solutions Inc.	RRC power solutions Ltd.	RRC power solutions Ltd.	RRC Power Solutions Company Ltd.
Technologiepark 1 66424 Homburg / Saar	18340 Yorba Linda Blvd., # 107-437 Yorba Linda, CA 92886	S-V,6/F, Valiant Industrial Centre 2-12 Au Pui Wan Street Fo Tan, N.T., Hong Kong	Room 1306, C Building, Tianan International Build- ing, Renmin South Road, Luohu District, Shenzhen	Block C, Lot CN4 Dinh Vu – Cat Hai Economic Zone,
+49 6841 98090 sales@rrc-ps.com	+1 714 777 3604 usa@rrc-ps.com	+852 2376 0106 hkrrc@rrc-ps.cn	518021 +86 755 8374 1908 hkrrc@rrc-ps.cn	Dong Hai 2 Ward Hai An District 180000 Hai Phong City
				vietnam@rrc-ps.com

