

## RRC1120

Standard Battery Pack Li-Ion

3.60V / 2.35Ah / 8.46Wh

P/N: 110018



Picture only for reference



### Features

- Worldwide approvals and certification of safety standards
- No development costs, fast time-to-market
- Smart battery with numerous features and I<sup>2</sup>C communication
- State-of-the-art lithium-ion cell with the market’s highest energy density
- High discharge performance
- JEITA charging profile optimization
- Numerous and redundant safety features
- Increased ESD protection up to 8.00kV
- Up to 80% of initial capacity after 800 cycles

### Applications

Suitable for use with hand held compact devices in industrial and medical areas, etc.

## Specification



General	
Delivery status battery capacity	<30%
Compliance information	IEC 62133 / CE / UL2054 / FCC / CAN ICES-003(B) / NMB-003(B) / UKCA / PSE / KC / BSMI / GOST-R / CMIM / CQC / RCM / BIS / TISI / UN 38.3 / RoHS / REACH
Operating temperature	0°C to 45°C (charge) -20°C to 60°C (discharge)
Storage temperature	-20°C to 60°C max. -20°C to 25°C recommended

Electrical Parameters	
Nominal voltage	3.60V
Nominal capacity	2.35Ah
Initial impedance	<100mΩ @ 1kHz at 25°C
Max. charge current	1.59A
Max. charge voltage	4.20V
Max. discharge current	2.30A

Battery Dimensions	
Length	52.50mm +0.20/-0.20
Width	34.95mm +0.15/-0.15
Thickness	11.15mm +0.10/-0.10
Weight	42g
Contacts	SCL, +, SDA (ID), -
Ingress protection	IP40

Safety Features	
CUV (Cell Under Voltage)	Protection against deep discharge
COV (Cell Over Voltage)	Protection against over charge
OTC (Over Temperature in Charge)	Protection against overheating while charging
OTD (Over Temperature in Discharge)	Protection against overheating during discharging

**Recommended Accessories**

Type	Product	P/N	Application
Standard Battery Charger 	RRC-SCC1120	110001	5.00W standard battery charger for optimized charging process with external power supply for worldwide use.
Battery Mating Connector 	RRC-MC11-90-2	210520	Mating Connector for standard semi smart batteries RRC1120, RRC1130. Available for 90° PCB mounting.

**Germany/Headquarters**

RRC power solutions GmbH  
Technologiepark 1  
66424 Homburg / Saar

Tel.: +49 6841 98090  
Fax: +49 6841 9809280  
Email: sales@rrc-ps.de  
Web: www.rrc-ps.com

**USA**

RRC power solutions Inc.  
18340 Yorba Linda Blvd.,  
# 107-437  
Yorba Linda, CA 92886

Tel.: +1 714 777 3604  
Fax: +1 714 777 3658  
Email: usa@rrc-ps.com  
Web: www.rrc-ps.com

**Hong Kong**

RRC power solutions Ltd.  
S-V,6/F, Valiant Industrial  
Centre 2-12 Au Pui Wan Street  
Fo Tan, N.T., Hong Kong

Tel.: +852 2376 0106  
Fax: +852 2375 0107  
Email: hkrrc@rrc-ps.cn  
Web: www.rrc-ps.cn

**China**

RRC power solutions Ltd.  
Room 1306, C Building,  
Tianan International building,  
Renmin South Road, Luohu  
District, Shenzhen 518021

Tel.: +86 755 8374 1908  
Fax: +86 755 8374 1861  
Email: hkrrc@rrc-ps.cn  
Web: www.rrc-ps.cn