

## RRC-SMB-FPC

Standard battery charger  
for smart batteries

P/N: 110083



### Features:

- 40W single-bay charger
- For the standard battery form factors RRC21xx or smart batteries with a similar footprint
- Optimized charging process for RRC batteries:
  - Longer cycle life
  - Faster charging
- Simple operation – Plug and Play
- External power supply for worldwide use
- Country-specific AC input cables available

### Applications:

Standard charging station for mobile devices used in medical, industrial and consumer markets



## Characteristics

Input		
Voltage range	18.00 – 26.00VDC	
Current	2.50A max.	
Power	40.00W	
Protection	Over-current (fuse protected), under voltage	
Output		
Voltage range	0 - 17.40VDC	
Current range	0 - 4.00A	
Voltage tolerance	±1% max.	
Current tolerance	±10% max. @1.00A, ±3% max. @4.00A	
Charge power	40.00W max.	
Protection	Short circuit, over temperature shutdown, input-/output over current	
Environmental		
	Operation:	Storage:
Ambient Temperature	0°C to 40°C	-30°C to 80°C
Pressure and Altitude	1060hPa to 795hPa -382m to 2000m	1060hPa to 533hPa -382m to 5000m
Humidity (non-condensing)	8% to 90% r.H.	5% to 95% r.H.
General		
Efficiency	~95% at 100% load	
Indicator	Multi-color LED (green, red, orange)	
Battery types	Standard battery form factors RRC21xx or smart batteries with a similar footprint	
Green procurement	RoHS 2011/65/EU + 2015/863/EU REACH 1907/2006 WEEE 2012/19/EU Chinese RoHS	
Cooling	convection cooled	
LED Indications		
One time Red/Orange/Green	Self-test: Charger is ready for use.	
Red/Green blinking	Battery recognition and initialization.	
Orange light	The inserted battery is of the correct type and is currently being charged.	
Green light	The battery is charged and can be removed for use.	
Red blinking	The battery is too hot or too cold to be charged without damage. If the battery is too cold it will be charged as soon as it has warmed up sufficiently. If the battery is too hot it should be removed to cool down.	
Red light	The battery is damaged or it is a conventional battery which cannot be recharged.	
Charger Mechanical Details		
Housing dimensions (LxWxH)	88.5 x 38.5 x 19.9mm	
Weight	36g (excluding power supply)	
Safety & EMC		
Regulatory approvals	Europe	EN62368-1 (CE)
	International	IEC62368-1 (CB)
Electromagnetic Emissions	Europe	EN55032
	USA	FCC15 class B
Electromagnetic Immunity	ESD immunity	EN/IEC61000-4-2
	Electromagnetic field immunity	EN/IEC61000-4-3
	EFT / Burst	EN/IEC61000-4-4
	Surge	EN/IEC61000-4-5
	Conducted Immunity	EN/IEC61000-4-6
	Voltage dips, short instrumentations & voltage variations	EN/IEC61000-4-11
	Harmonic current emissions	EN 61000-3-2
	Voltage changes, voltage fluctuations and flicker	EN 61000-3-3
	Immunity characteristics	EN55035

## Specification external AC/DC power supply

Input		
Voltage range	100.00 – 240.00VAC ±10%, 50-60Hz	
Current	1.70A max.	
Stand by power	< 0.21W @ no load	
Output		
Voltage range	19.00VDC ± 5%; Ripple < 300mV <sub>pk-pk</sub>	
Power	65.00W max.	
Current range	3.42A max.	
Protection	Short circuit, over voltage, over current, over temperature	
General		
Efficiency	California's Energy Efficiency Level VI	
Ripple & Noise	300mV (p-p)	
Power Supply Mechanical Details		
Standard output connector	DC barrel jack, 5.5 x 2.5 x 11mm	
Housing dimensions (LxWxH)	95 x 50 x 25.4mm	
Weight	270g	
Cable length	1600mm ±50mm	
Regulatory Approvals		
Approvals	Europe International USA & Canada Australia & New Zealand Russia (Customs Union) Korea China Japan India Taiwan Mexico Singapore United Kingdom Morocco	CE CB cULus RCM EAC KC CCC PSE BIS BSMI NOM Safety Mark UKCA CMTM

## Recommended Accessories

Type	Product	P/N	Application	
3-pol AC-Cable		US-Version	Country-specific power cable for standard battery chargers from RRC and PS65.	
	EU-Version	210951		
	UK-Version	211133		
	AU-Version	211134		
	CN-Version	211959		
Car Adapter DC/DC		RRC-SMB-CAR	110041	90W car adapter with USB charging port. Power supplying in cars and trucks for standard battery chargers and power management modules from RRC or mobile devices.

### Germany/HQ

RRC power solutions GmbH  
Technologiepark 1  
66424 Homburg / Saar

+49 6841 98090  
sales@rrc-ps.com

### USA

RRC power solutions Inc.  
18340 Yorba Linda Blvd.,  
# 107-437  
Yorba Linda, CA 92886

+1 714 777 3604  
usa@rrc-ps.com

### Hong Kong

RRC power solutions Ltd.  
S-V,6/F, Valiant Industrial  
Centre 2-12  
Au Pui Wan Street  
Fo Tan, N.T., Hong Kong

+852 2376 0106  
hkrrc@rrc-ps.cn

### China

RRC power solutions Ltd.  
Room 1306, C Building,  
Tianan International Building,  
Renmin South Road,  
Luohu District, Shenzhen  
518021

+86 755 8374 1908  
hkrrc@rrc-ps.cn

### Vietnam

RRC Power Solutions  
Company Ltd.  
Block C, Lot CN4  
Dinh Vu – Cat Hai  
Economic Zone,  
Dong Hai 2 Ward  
Hai An District 180000  
Hai Phong City

vietnam@rrc-ps.com